

(19) World Intellectual Property Organization
International Bureau



PCT



(43) International Publication Date
25 September 2008 (25.09.2008)

(10) International Publication Number
WO 2008/116123 A1

(51) International Patent Classification:
H04N 5/445 (2006.01)

(21) International Application Number:
PCT/US2008/057763

(22) International Filing Date: 20 March 2008 (20.03.2008)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/895,966 20 March 2007 (20.03.2007) US

(71) Applicant (for all designated States except US): **SPUD-
NIK, INC.** [US/US]; 135 Riviera Drive, Apt. 435, Los
Gatos, CA 95032 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **JAIN, Amit**
[US/US]; 1161 Mariani Drive, Sunnyvale, CA 94087
(US). **MUNDKUR, Yatin** [US/US]; 25625 O'Keefe Lane,
Los Altos Hills, CA 94022 (US). **HAJJAR, Roger, A.**
[US/US]; 1050 Camino Ricardo, San Jose, CA 95125
(US).

(74) Agent: **AI, Bing**; P.O. Box 1022, Minneapolis, Minnesota
55440-1022 (US).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA,
CH, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE,
EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID,
IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC,
LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN,
MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PG, PH,
PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, SV,
SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN,
ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MT, NL,
NO, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG,
CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).


Declaration under Rule 4.17:

— as to applicant's entitlement to apply for and be granted a
patent (Rule 4.17(ii))

Published:

— with international search report

(54) Title: DELIVERING AND DISPLAYING ADVERTISEMENT OR OTHER APPLICATION DATA TO DISPLAY SYS-
TEMS



(57) Abstract: Display devices and systems including television sets, and systems, apparatus and methods for delivering information and providing services through display devices and systems. The display used in the described systems and methods is capable of receiving one or more TV programming channels and an independent designated application channel and having at least a first display window and a second display window separated from each other without spatial overlap on the screen. The information sent over the designated application channel to the display is displayed on the first display window while simultaneously displaying one of the TV programming channels on the second display window. A viewer control mechanism is provided in the display to allow the viewer to switch the information received from the designated application channel from the first display window to the second display window and switch back at the viewer's choice.

**DELIVERING AND DISPLAYING ADVERTISEMENT OR OTHER APPLICATION
DATA TO DISPLAY SYSTEMS**

PRIORITY CLAIM AND RELATED PATENT APPLICATION

5 **[0001]** This application claims the benefit of U.S.
Provisional Application No. 60/895,966 entitled "Delivering
and Displaying Advertisement or Other Application Data to
Display Systems" and filed on March 20, 2007, which is
incorporated by reference as part of the specification of this
10 application.

BACKGROUND

[0002] This application relates to display devices and systems
including television sets, and systems, apparatus and methods
15 for delivering information and providing services through
display devices and systems.

[0003] Display devices and systems include at least one
display screen to display still and moving images and can be
configured in a wide range of configurations based on
20 different display technologies. Some examples of display
devices and systems include, among others, television (TV)
sets, desktop and mobile computers, mobile digital devices
such as some mobile phones and personal digital assistant
(PDA) devices, and indoor and outdoor large displays such as
25 large format displays and digital billboards installed at New
York City's Times Square and other locations.

[0004] Display devices and systems can be configured to
receive information to be displayed through one or more
sources. TV sets, for example, can receive TV programming
30 through one or more designated TV signal channels, e.g., (1) a
TV broadcast radio signal over the air from a TV station, (2)
a TV cable from a TV cable service network, (3) a satellite TV
broadcast signal from a TV broadcast satellite, and (4) TV
broadcast data from a computer networks such as the Internet.
35 A TV programming provider, such as a cable TV service provider

or a satellite TV service provider, can provide many different channels of TV programming to a subscriber's TV set.

SUMMARY

5 **[0005]** This application describes, among others, display devices and systems including television sets, and systems, apparatus and methods for delivering information and providing services through display devices and systems.

10 **[0006]** In one aspect, a method for delivering information to a display is described to include establishing a communication link with a display, which receives one or more TV programming channels and an independent designated application channel and includes at least a first display window and a second display window separated from each other without spatial overlap on
15 the screen, to send data of the independent designated application channel to the display. The communication link is separate from one or more communication links that deliver the one or more TV programming channels to the display. This method also includes delivering information over the
20 designated application channel to the display to display in the first display window while simultaneously displaying a TV programming channel on the second display window.

25 **[0007]** In another aspect, a method for delivering information to a display is described to include providing a display capable of receiving one or more TV programming channels and an independent designated application channel and having at least a first display window and a second display window separated from each other without spatial overlap on the screen; and delivering information over the designated
30 application channel to the display to be displayed on the first display window while simultaneously displaying one of the TV programming channels on the second display window. This method may include providing a viewer control mechanism to allow the viewer to switch the information received from

the designated application channel from the first display window to the second display window and switch back at the viewer's choice.

[0008] In another aspect, a display system is described to include a screen to display images; at least one TV and video input to receive a TV or video input channel for display on the screen; a designated application channel receiver to receive a designated application channel that is independent from a broadcast TV programming channel; a local memory that stores data received in the designated application channel; and a display controller to control each frame displayed on the screen to have a first display window at a first location on the screen that displays the TV or video input channel and a second window at a second location without overlap with the first display window that displays the stored data in the designated application channel. The display controller includes a switch mechanism to switch displayed contents between the first and the second display windows.

[0009] In another aspect, a system is described to include a communication network to provide communications to devices in communication with the communication network; a designated application channel computer server in communication with the communication network to send out data of a designated application channel that is independent from a broadcast TV programming channel; and a display system. The display system includes a designated application channel receiver in communication with the communication network to receive the data of the designated application channel, a local memory to store the received data, a screen to display images, a display controller to retrieve the stored data from the local memory and to display the retrieved data on the screen, and a TV programming receiver to receive the broadcast TV programming channel. The display controller operates to control each frame displayed on the screen to simultaneously display the

stored data in the designated application channel and the broadcast TV programming channel on the screen.

[0010] In yet another aspect, a method for sending TV advertisements to TV viewers is described to include
5 delivering a designated application channel, that is separated from TV programming channels, through a communication network to networked displays equipped to receive the designated application channel and TV programming channels. This method also includes using one or more computer servers in
10 communication with the communication network to supply selected TV advertisements over the designated application channel without TV programming to each of the networked displays based on viewer profile information of one or more TV viewers associated with the respective networked display.

[0011] These and other aspects and implementations can be used to achieve one or more advantages. For example, the designated application channel and associated display features can be provided to advertisers or other information or service providers to directly access TV viewers without using TV
20 programming providers. For another example, the designated application channel and associated display features can be used to provide targeted delivery of information and services to a viewer based on the viewer profile and may be used to allow for interactions with the viewer to provide information
25 and services on demand. For yet another example, the designated application channel and associated display features can be used to provide new or alternative services to TV viewers that may not be available from TV programming providers.

[0012] These and other aspects and implementations and associated advantages are described in greater detail in the drawings, the detailed description and claims.

BRIEF DESCRIPTION OF DRAWINGS

[0013] FIG. 1 illustrates an example of a display device (e.g., a TV set) that has two or more display windows on the screen and is designed to receive the designated application channel.

[0014] FIG. 2 shows an example of the TV display controller in FIG. 1.

[0015] FIGS. 3A and 3B show two display modes of a screen in FIG. 1.

[0016] FIGS. 4A, 4B, 4C, 4D, 4E and 4F show examples of screen partitions of a screen in FIG. 1.

[0017] FIGS. 5A and 5B illustrate one example of display devices for FIG. 1.

[0018] FIG. 6 illustrates how the TV set in FIG. 1 is operated to deliver content to TV viewers.

[0019] FIG. 7 illustrates one example of a system level implementation for providing the viewer feedback through a communication network to which the designated application channel computer server is either directly connected or indirectly connected through another communication network.

[0020] FIG. 8 shows an example of a graphic user interface for the designated application channel.

[0021] FIGS. 9A and 9B show examples of business models in marketing TV sets in FIG. 1 and associated services through the designated application channel.

[0022] FIG. 10 shows an example of a scanning laser display system where two laser modules and 510B implemented to project images in two display windows on a common screen, respectively.

DETAILED DESCRIPTION

[0023] In many TV programming channels, the delivered content of a TV programming channel is often controlled by the TV programming provider for that particular channel. For

example, the programming provider for a sports channel often exclusively controls all the content in the sports channel, including sports programs, news and commercials. The TV viewer who receives or subscribes the sports channel usually has no control over the programming content in the sports channel and the programming content and the commercials interleaved with programming content are pre-packaged by the programming provider and are sent to all subscribed viewers for the sports channel. For some programming channels such as interactive channels or video-on-demand channels, the TV viewer may select a portion of the content controlled by the TV programming provider but the content of the channel often remains under the sole control of the TV programming provider.

[0024] Examples described below provide display devices and systems such as TV sets that allow for receiving a designated application channel that is independent of a TV programming channel and has a display screen that displays both the designated application channel and the TV programming channel selected by the viewer in two or more separate display windows on the screen.

[0025] In one implementation, the hardware and software are implemented in the present display devices and systems to allow reception of the designated application channel from a source that is separate from a source for a TV programming channel. For example, a TV programming channel may come from a cable or satellite TV channel while the designated application channel is provided by a designated application channel computer server in communication with the Internet, a wireless communication network (a cellular network based on GSM, CDMA, WiMax, WiFi or other wireless communication standards) or other communication networks. For another example, both a TV programming channel and the designated application channel may come from the Internet but the designated application channel computer server is separated

from and is independent of a computer server on the Internet that provides the TV programming channel. The designated application channel computer server can be directly connected to the communication network that delivers the designated application channel to the viewer's TV set or is connected to a separate network (e.g., an IP communication network) that is connected to the communication network that delivers the designated application channel to a viewer's TV set. The designated application channel can be used to provide various information and services to the TV set for the viewer, e.g., advertisements, alternative TV programming, video conference service, telephone calls, access to various databases or the Internet, access to controlling of on-line appliances, on-line banking, on-line shopping, and others. This designated application channel is independent from a TV programming channel and can make the TV viewer be accessible by other information providers and service providers through the designated application channel computer server.

[0026] Such a system based on the designated application channel and display devices and systems capable of receiving the designated application channel and displaying two or more separate windows on a screen can be used to create new uses and applications of TV sets and other display systems, including individualized TV advertising and other individualized application services. In some implementations, a TV viewer can use the TV set to access the designated application channel computer server to provide or update user profile data, to request for or change individualized services such as certain selected advertisements, or to access an application such as conducting a telephone call or video call, controlling an Internet-connected appliance, or accessing an Internet website.

[0027] FIG. 1 illustrates an example of a display device 100 (e.g., a TV set) that has two or more display windows on the

screen and is designed to receive the designated application channel in addition to receiving one or more TV programming channels. The display technology for the device 100 may be based on various display technologies. Examples of some flat panel display technologies include plasma flat panel displays, LCD flat panel displays, field emission display (FED) flat panels and organic light emitting diode (OLED) display panels. Examples of some front and rear projector displays include CRT projectors, LCD projectors, digital light processing (DLP) projectors, digital direct drive image light amplifier (D-ILA) projectors, liquid crystal on silicon (LCOS) projectors and scanning beam fluorescent or phosphorescence displays.

[0028] In FIG. 1, the TV set 100 includes a TV display screen 110 to display images. The TV display screen 110 can be a single screen that includes a large main display window 111 and one or more separate small supplemental display windows 112. The example in FIG. 1 shows one small supplemental display window 112 on the lower part of the screen 110. In some implementations, the main display window 111 and the supplemental display window 112 can be spatially separated display windows without overlap with each other. Therefore, different from overlapped pop-up windows commonly seen on computer desktops and picture-in-picture features in TV sets, the content display in each window in such implementations is free of obstruction by the other display window.

[0029] The main display window 222 can be a HDTV display window with an aspect ratio of 16:9 that supports a desired HDTV resolution, such as 720 line progressive scan (720p), 1080 interlaced scan (1080i), 1080 progressive scan (1080p) or other HDTV resolution formats. The supplemental display window 112 can be smaller in size and can be configured to have the same image pixel size as the main display window 111 when both display windows are generated on the same screen using the same display technology, e.g., a LCD display, a

plasma display, a projection display or a scanning-beam display. Alternatively, the supplemental display window 112 may be configured to have a different pixel size from the main display window by using either the same display technology as the main display window 111 or a different display technology. For example, a lower resolution slower response low cost technology maybe used for ad-specific applications in the supplemental display window 112.

[0030] The TV set 100 in FIG. 1 includes a TV display controller 140 for the dual-window screen that processes the designated application channel input 122 and a TV/video channel input 130 and to display the two channels on the two display windows 111 and 112, respectively. A user remote control unit can be used by the TV viewer to switch either of the designated application channel 122 and the TV/video channel 130 onto the main display window 111. An application channel receiver (RX) or transceiver (RX/TX) 120 is provided to receive a designated application channel signal 121 from a source outside the TV set and to output a designated application channel input signal 122 to the TV display controller 140. The application channel receiver or transceiver 120 can be designed to receive the designated application channel signal 121 in one or more formats, such as a wireless RF signal from a ground RF communication network (e.g., a cellular network), a cable communication network, a WiFi communication channel or network under IEEE 802.11, a WiMax communication network, a digital subscriber line (DSL) over a telephone network, and an RF communication signal from a satellite.

[0031] FIG. 2 shows an example of the TV display controller 140 in FIG. 1. The controller 140 includes a memory device 241 that stores data from the application channel input and the TV/video channel. The memory device 241 may be two separate memory devices 242A and 242B to separately store

TV/video data and the application channel data. The data in the received application channel input 122 is received and processed by an application processing unit 241 and is then stored in the memory 242 (e.g., the application channel memory 242A). The application processing unit 241 is provided and configured to process the application channel data for display on the screen. The TV/video channel input 130 selected by the viewer is sent to a TV/video processing unit 243 for processing and the processed data is used for display on the screen. A TV/Video memory device 242B can be provided to store the processed TV/Video data for later retrieval for display on the screen. A display controller 244 is provided to combine the processed application channel data and the TV/video channel data to produce a display control signal 245 that controls the screen to display the two channels in the two different windows. In some implementations, at least two of the application channel processing unit 241, the TV/video processing unit 243 and the display controller 244 may be integrated as a single chip. For example, all three functions may be integrated into a single controller.

[0032] In one implementation, the display controller 244 uses the data from the designated application channel and the data from a viewer-selected TV programming channel to form the frame data for each frame to be displayed on the screen. A raster scanning mechanism can be used to render the images on the screen. In such a raster scan in scanning through horizontal lines from the top of the screen to the bottom of the screen in displaying one frame, the contents in the two display windows can be embedded in the pixel data for each frame and are sent to the screen during the scans in a frame. At the end of one frame scan and prior to the next frame scan, the display controller performs a vertical retrace in a period known as the vertical blanking interval, the display controller does not send out data from the designated

application channel and the data from a viewer-selected TV programming channel. At the end of the vertical blanking interval, the display controller resumes sending out the data from the designated application channel and the data from a viewer-selected TV programming channel in the next frame scan.

[0033] In operation, the TV viewer can select either of the application channel and the TV/video channel to be shown in the main display window 111. Referring to FIG. 3A, in a "normal" display mode, the viewer can select the main display window 111 to show the TV/video channel while displaying the application channel in the supplemental display window 112. The application channel may be displayed in the supplemental display window 112 in a reduced version, e.g., text of a commercial without the full images or video or sound in the commercial. When the viewer switches the application channel to be displayed in the main display window 111, the full version of the content of the application channel is displayed, e.g., a commercial with sounds and video or images. Hence, under the normal display mode, the TV/video channel data can be sent directly to the TV/video processing without being stored in the memory. Alternatively, the TV/video channel data can be sent directly to the TV/video processing for display while being simultaneously stored in the memory in a circular storage mode to overwrite the oldest data when the storage is full. When the viewer sees a commercial of a particular interest, the viewer can use the TV remote control unit to switch the application channel to the main display window 111. This is the application display mode as shown in FIG. 3B. Upon switching, the received data stream of the TV/video channel is stored in the memory and the TV/video processing unit generates a flag to indicate the location of the video stream where the switching occurs. When the viewer switches the TV/video channel back to the main display window 111, the TV/video processing unit retrieves the stored

TV/video data from the memory and begins to display from the location of the video stream marked by the flag.

[0034] In some implementations, the display controller 244 can be configured to allow a viewer to send requests or feedback 123 via an viewer interface menu on the screen by using, e.g., the viewer remote control. The data for the viewer request or feedback 123 is sent by the application processing unit 241 to the application channel transceiver 120 which further transmits the viewer data to a remote application computer server that supplies the application channel input 122. The remote application computer server can be connected to a communication network through which the data is delivered between the TV and the remote application computer server.

[0035] The partition of the screen into at least two display windows shown in FIGS. 1, 3A and 3B is one of various partition configurations. FIGS. 4A,-4D show four other screen partition examples where X represents the main display window 111. In FIG. 4A, the main display window 111 is at the center of the screen while the supplemental windows 112 are at peripheral areas A and B at four sides of the screen. In FIG. 4B, the main display window 111 is at the center of the screen fully occupying the screen along the horizontal direction while the supplemental windows 112 are at peripheral areas B at upper and lower sides of the screen. In FIG. 4C, the main display window 111 is at the center of the screen fully occupying the screen along the vertical direction while the supplemental windows 112 are at peripheral areas A at left and right sides of the screen. In FIG. 4D, the main display window 111 is off the center of the screen while the supplemental window is 112 at peripheral areas at two adjacent sides of the screen.

[0036] FIG. 4E shows a screen partition example where a 1920Vx1560H screen is partitioned into a 1920Vx1080H main display window and three 640Vx480H supplemental display

windows on the bottom of the screen. The supplemental display windows are used for simultaneously showing advertisements in text, advertisements in video and a browser interface.

[0037] FIG. 4F shows a screen partition example where a screen
5 with 2400 vertical lines and 1440 horizontal lines is divided
in to a 1920Vx1080H main display window and multiple
supplemental display windows. The multiple supplemental
display windows include two 480Vx540H windows vertically
stacked on the right-hand side of the main display window,
10 three 640Vx360H supplemental display windows horizontally
lined up below the main display window and a 480Vx360H
supplemental window at the right lower corner of the main
display window. These supplemental windows are used for
simultaneously showing different TV advertisements and an
15 online help interface.

[0038] In some applications, the TV set in FIG. 1 may include
a video camera (e.g., a web cam) located at one side of on the
screen and may provide a microphone on the TV set, the user
remote control or the video camera for video conference
20 applications and other applications that deliver images from
the TV set to a remote destination through the designated
application channel. For example, such applications can be
provided to customers who wish to buy time on the designated
application channel.

25 **[0039]** FIGS. 5A and 5B show an example of a scanning-beam
fluorescent screen for implementing the TV sets shown in FIGS.
1-4D. At least one scanning laser beam 520 is used to excite
color light-emitting materials deposited on a screen 501 to
produce color images. The scanning laser beam 520 is
30 modulated to carry images in red, green and blue colors or in
other visible colors and is controlled in such a way that the
laser beam excites the color light-emitting materials in red,
green and blue colors with images in red, green and blue
colors, respectively. Hence, the scanning laser beam 520

carries the images but does not directly produce the visible light seen by a viewer. Instead, the color light-emitting fluorescent materials on the screen 501 absorb the energy of the scanning laser beam and emit visible light in red, green and blue or other colors to generate actual color images seen by the viewer.

[0040] FIG. 5A illustrates an example of a laser-based display system using a screen having color phosphor stripes.

Alternatively, color phosphor dots may also be used to define the image pixels on the screen. The system includes a laser module 510 to produce and project at least one scanning laser beam 520 onto a screen 501. The screen 501 has parallel color phosphor stripes in the vertical direction where red phosphor absorbs the laser light to emit light in red, green phosphor absorbs the laser light to emit light in green and blue phosphor absorbs the laser light to emit light in blue.

Adjacent three color phosphor stripes are in three different colors. One particular spatial color sequence of the stripes is shown in FIG. 1 as red, green and blue. Other color

sequences may also be used. The laser beam 520 is at the wavelength within the optical absorption bandwidth of the color phosphors and is usually at a wavelength shorter than the visible blue and the green and red colors for the color images. As an example, the color phosphors may be phosphors that absorb UV light in the spectral range from about 380 nm to about 420 nm to produce desired red, green and blue light. The laser module 510 can include one or more lasers such as UV diode lasers to produce the beam 520, a beam scanning mechanism to scan the beam 520 horizontally and vertically to render one image frame at a time on the screen 501, and a signal modulation mechanism to modulate the beam 520 to carry the information for image channels for red, green and blue colors. Such display systems may be configured as rear scanner systems where the viewer and the laser module 510 are

on the opposite sides of the screen 501. Alternatively, such display systems may be configured as front scanner systems where the viewer and laser module 510 are on the same side of the screen 501.

5 **[0041]** FIG. 5B further shows the operation of the screen 101 in a view along the direction perpendicular to the surface of the screen 501. Since each color stripe is longitudinal in shape, the cross section of the beam 520 may be shaped to be elongated along the direction of the stripe to maximize the
10 fill factor of the beam within each color stripe for a pixel. This may be achieved by using a beam shaping optical element in the laser module 510.

[0042] The laser module 510 may use a vertical scanning mirror and a rotating polygon mirror to provide the 2-dimensional
15 scanning of one or more scanning beams on the screen to form images. A beam may be first directed to the vertical scanning mirror and then to the horizontal polygon mirror or in a reverse order. In operation, in tracing a horizontal line by scanning the polygon scanner, the vertical scanning mirror
20 operates to displace the horizontal lines vertically. The vertical scanning mirror can be implemented by, e.g., using a mirror engaged to a galvanometer as the vertical scanner.

[0043] The above scanning-beam display design can be used to achieve large displays (e.g., 60" or above) with high
25 resolutions (e.g., 1080p HDTV resolution) at relatively low costs. For example, a large fluorescent screen can be built with extra space around the standard feature size (HD 1080p today) where the extra space can be used to provide for the supplemental display window on any side of the screen. The
30 fluorescent screen can be designed to be efficient in generating colored light under optical excitation of the scanning beam. Therefore, such scanning type displays, when properly designed and engineered, can have low power

consumption and a long lifetime. As the result, the application channel can be in an "always on" mode.

[0044] Notably, the application channel is separated from TV programming channels received from cable, satellite or other sources in the above TV sets and hence can be used by a party other than the TV programming providers or Internet service providers to have access to TV viewers. The TV sets with one or more supplemental display windows can be designed to deliver the content in the designed application channel to one or more supplemental display window while showing a viewer selected TV program in the main display window. The control of the TV set allows a viewer to switch the content of the designed application channel to the main display window as the viewer desires. The designated application channel can be a passive advertisement channel to deliver various TV advertisements to the viewer in some implementations. Alternatively, the designated application channel can be "interactive" to allow the viewer to access a website featuring the product or service advertised in the TV ads through the designated application channel so that the viewer can obtain additional information on that advertised product or service and other products and services offered on the website and may use the TV remote control and on-screen user interface menu to make a purchase on the website.

[0045] One application for the designated application channel is a TV advertisement system that is independent of TV programming channels subscribed by the TV viewers and a ISP from which the view obtains high-speed Internet access. Information of the viewers may be obtained during sale of the TV sets and such viewer information can be used to tailor the information content in the designed application channel to fit certain criteria of the viewer profile. For example, the TV advertisements delivered via the designated application

channel may be made contextual to the viewer profile to provide targeted or personalized TV ads.

[0046] Many other applications can also be implemented through the designated application channel. For example, video
5 conference services may be provided, where a viewer uses an on-screen video conference call application delivered through the designated application channel to the TV set and a video camera on the TV set to conduct video conference calls. For another example, a telephone call service may also be provided
10 through this system.

[0047] The content of the designated application channel can be minimized or simplified when displayed in the small supplemental display window of the TV screen. This is to reduce distractions when the main display window is playing a
15 TV program from one of the TV channels. For example, the content of the designated application channel in the supplemental display window may be displayed as a text or a small logo and may also be changed less frequently over time such as displaying one image or text no more than once a
20 minute.

[0048] In some implementations, the supplemental display window can be used to allow the user to display another channel using the supplemental display as "picture in picture" with overlay of advertisement. This feature can be used to
25 entice the user to use the extra display space to select channels. In this hardware implementation, the extra display is connected to the incoming TV channel while mixing it with advertisement space on the side.

[0049] In some implementations, a cellular network may be used
30 to deliver the designated application channel to the TV set in FIG. 1 where the application channel receiver or transceiver is a wireless subscriber station in the cellular network. To efficiently use the limited cellular bandwidth, the content of the designated application channel may be downloaded and

stored in the application memory unit during a period where there is less traffic (e.g., late night or early morning).

The stored data can be later retrieved from the memory and displayed the screen when the TV is turned on. Other

5 communication networks may be used to deliver the designated application channel such as the Internet, a WiMax

communication network, or a WiFi network. On the Internet,

various technologies for distribution of multimedia data including video may be used to deliver the designated

10 application channel, including data distribution technologies provided by Ortiva Wireless (<http://www.ortivawireless.com>)

and Akamai Technologies, Inc (<http://www.akamai.com>).

[0050] FIG. 6 illustrates an example for using the TV set in FIG. 1 to deliver content to TV viewers. A TV set which is

15 capable of receiving one or more TV programming channels and an independent designated application channel and having at

least a first display window (supplemental display window) and a second display window ("main display window") on the same

screen is provided (step 610). The hardware described in

20 FIGS. 1 and 2 is included in this TV set. Information that is separated from TV programming is delivered over the designated

application channel to the TV set to be displayed on the first display window, the supplemental display window, on the screen

while allowing the TV set to simultaneously display one of the

25 TV programming channels on the second display window, the main display window (step 620). In one implementations, a viewer

control mechanism such as a TV remote control and related control circuitry in the TV can be provided to allow the

viewer to switch the information received from the designated

30 application channel from the first display window to the

second display window and switch back at the viewer's choice

(step 630).

[0051] The designated application channel can be configured to allow a TV viewer to provide viewer feedback through a user

graphic interface to the designated application channel computer server to send viewer requests and data and to access other resources through the designated application channel computer server. FIG. 7 illustrates one example of a system level implementation for providing the viewer feedback through a communication network to which the designated application channel computer server is either directly connected or indirectly connected through another communication network.

[0052] In FIG. 7, the designated application channel computer server can be implemented by one or more computer servers 710. The communication network 701 can be one or more connected communication networks. A wireless communication network, e.g., a wireless cellular network, can be used to implement the network 701. An advertiser can use an advertiser computer server 720 in communication with the network 701 to deliver its advertisements to the designated application channel computer server 710 and such advertisements are stored in the server 710. Multiple advertisers can send and store their advertisements in the server 710. The server 710 can selectively request advertisements from advertisers via their servers 720 based on the viewer requests or its need to send targeted advertisements to viewers. A user TV set or other display system 730 is connected in communication with the network 701 via the transceiver 120 to send out viewer request or data and to receive the selected advertisements from the server 710 via the network 701.

[0053] The designated application channel computer server 710 stores viewer profile data, viewer requested advertisements and selected advertisements that retrieved from advertiser computer servers 720 based on viewer profile data of various viewers. These stored advertisements are sent to respective viewers via the network 701. At the viewer side, each TV set 730 includes a local memory that stores data related to the designed application channel. Referring back to FIG. 2, the

application memory 242A is designated to store such data which can include, for example, the local viewer profile data, advertisement data and other data that are received from the designated application channel computer server 710. The application processing module 241 in FIG. 2 is programmed to perform advertisement heuristic methods for delivering advertisements to the TV screen by using the viewer profile to push selected advertisements from the server 710 to the TV screen without the viewer requests or by responding to the user requests to retrieve user requested advertisements from the server 710 for displaying on the TV screen. The local stored advertisement data in the TV set 730 may be formatted in different content types so that each advertisement is available in multiple formats. For example, an advertisement can be stored in a plain text format with a hyperlink for scrollable text mode, a flash animation format to be displayed in the supplemental display window and a high-definition quality video format to be shown in the main display window. Referring to the screen partition in FIG. 4E, the supplemental display windows in that example can be used to show ads in text and ads in flash animation video. A viewer at the 730 can use the TV remote control 740 to call up the user graphic interface on the screen in either of the display windows, e.g., in the main display window and send various requests or viewer data to the designated application channel computer server.

[0054] FIG. 8 shows an example of a viewer menu to allow the viewer to use the remote control to send viewer information, e.g., data, preferences or requests, to the remote designated application channel computer server.

[0055] For example, a viewer can provide or update viewer data profile stored in the designated application channel computer server. The viewer profile data can be used by the designated application channel computer server to deliver selected

advertisements tailored based on the information in the viewer data profile. The viewer data profile may include demographic information of a viewer and interests, hobbies and habits of the viewer. For example, the viewer data profile may include
5 at least some of the following items on the viewer: age, gender, residence, occupation, information on homeownership or rental residence, income level, education, hobbies, family, interests in sports, art, books, music, films, food, wine, and future purchases. This feature can be used to provide
10 targeted advertisements to a group of users with certain demographic characteristics and, notably, to provide individualized advertisements tailored for each individual viewer. Such targeted advertising and individualized advertising can be difficult to achieve in conventional TV
15 programming channels and can open up new and direct advertising opportunities for advertisers. The combination of the designated application channel free of control by a TV programming provider and the display features provided by TV sets with two or more display windows in FIG. 1 provides a
20 direct contact between individual viewers and an advertiser.

[0056] The above user profile data can be obtained by requesting the user to provide such data. Referring to FIG. 2, the application processing module 241 can be configured to obtain certain data from the TV/Video processing module 243 to
25 capture the user's history of TV programming viewing preferences and habits. Such captured user's history of TV programming viewing preferences and habits can be used by the application processing module 241, either in combination with the user provided viewer profile data or independent from with
30 the user provided viewer profile data, to request and retrieve certain advertisements from the server 710 and to push such advertisements to the TV screen.

[0057] As another example, a viewer can request certain types of advertisements to be delivered through the designated

application channel to the viewer's TV set using the viewer feedback or requests to the designated application channel computer server 710. The user graphic interface can be desired to provide fields where the viewer can enter viewer requests for selected advertisements or provide choices of available advertisements for the viewer to select. In response to the viewer's selection, the selected advertisements are delivered to the viewer's TV set from the designated application channel computer server. Therefore, if the viewer wants to see all car advertisements, a viewer selection can be made. The viewer can also change the selection or specify the period for the selection.

[0058] The designated application channel can also be used as a link for a viewer to access the Internet. The viewer can use the user graphic interface to access the Internet using the TV remote control. For example, this feature can link the viewer to a website selling a product or service through the independent designated application channel when the viewer selects the product or service on the TV set displaying the designated application channel. During this operation, the designated application channel can be displayed in the main display window.

[0059] Different from a conventional TV programming channel where the programming content and advertisements are interleaved in different broadcast time slots, the designated application channel described here provides a designated channel that is independent from a TV programming channel and allows advertisers to directly deliver their advertisements to a viewer. This aspect of the present systems provides alternative and direct access to TV viewers with targeted and individualized advertising. Referring to FIG. 7, an advertiser can send advertisements from the advertiser's computer server 720 connected to the communication network 701 to the designated application channel computer server 710 to

be stored in a memory. This memory in the designated application channel computer server 710 can be an advertisement depository to store advertisements from different advertisers and are indexed for delivery to viewers. Referring to FIG. 2, the local memory 242 in the TV set stores the received advertisements and the stored advertisements are displayed in one of the two display windows when the TV set is turned on.

[0060] Various revenue generation mechanisms can be built in the present systems. For example, an advertiser can be charged a fee for placing one or more TV advertisements from the advertiser in the stored collection of advertisements. For another example, an advertiser can provide and store one or more TV advertisements in the stored collection of advertisements for free but is charged a fee every time one of the advertiser's advertisements is delivered to a TV viewer due to the viewer request or by other mechanisms that trigger the advertisement delivery to a user. For example, an advertisement can be sent to a viewer based on the viewer profile data collected in computer server for delivering the designated application channel. A combination of the above and other methods for charging advertisers may be used in some applications.

[0061] The above described TV sets can be sold to viewers with different options for receiving the content in the designated application channel. FIG. 9A illustrates business models where a TV buyer purchases the TV at a retail price and receives refund for agreeing to receiving the content from the designated application channel. In one implementation, the buyer can receive monthly, quarterly or other periodical payment for agreeing to receiving the designated application channel until the full purchase price is paid back to the buyer. In another implementation, the buyer may be given the option of getting only partial refund when the buyer wants to

terminate delivery of advertisements earlier. Without displaying the designated application channel, the screen area occupied by the supplemental display window is freed and may be used to provide an extra display area for the main display window (e.g., using the entire screen to show the main display window or allowing the user to zoom the main display window). In yet another implementation, the TV records the number of times that the TV is switched to the application display mode by showing the designated application channel and computes the amount of a periodic payment based on the amount of the time that the TV is in the application display mode. A buyer can also purchase the TV without agreeing to receive any information from the designated application channel. In this case, the supplemental display window can be designed to display the TV manufacture's logo or name.

[0062] FIG. 9B shows another business model where a TV buyer gets a free TV but agrees to receiving the designated application channel over a minimum amount of time (e.g., 2 years).

[0063] The above described video conference and telephone services delivered via the designated application channel are examples of various services that can be delivered through the designated application channel. Various other applications can be achieved based on the designated application channel, including on-line gaming, on-line premise security monitoring, localized on-line yellow page services, and monitoring telephone (including caller ID) services.

[0064] For example, the designated application channel can be used to send information on status of a telephone at the user's premise. The telephone, which may be an IP phone or a phone through the public telephone switch network via a telephone line, may be connected to the display unit via a cable or wirelessly. While watching TV, if the phone rings, the caller ID from the phone is delivered to the display

controller as part of data to be displaced on the supplemental display window on the screen. In operation, the display controller temporarily halts the display of the information in the designated application channel and displays the caller ID
5 in the supplemental display window. Based on the displayed caller ID, the viewer can decide whether to answer the call. The viewer may use the display equipped with speaker and microphone to take the incoming call via a telephone call user interface menu on the screen and the selection of answering
10 the call can automatically mute the sound of the TV/video channel. The viewer can make an outgoing call using the telephone call user interface menu in the supplemental display window while watching the TV/video channel in mute. A designated button on the viewer remote control may also be
15 used for the viewer to call up the telephone call user interface menu in the supplemental display window on the screen. Upon completing the call, the previously halted information in the designated application channel is resumed and is shown in the supplemental window.

20 **[0065]** Referring to FIG. 7, the designated application channel computer server 710 may be used to store phonebook-like information in various regions and, based on a viewer's location (e.g., zip code or address) in the user profile data to deliver on phonebook information the district or city of
25 the viewer. The viewer can send a request via the designated application channel to access local information, such as, restaurants, shops, hospitals, movies, and others by using the remote control. In one implementation, a designated icon for the phonebook-like information can be placed in a user
30 interface menu or a selective location in the supplemental display window and the user can use the remote control to select and call up the user interface menu for the phonebook-like information. Alternatively, a designated key on the remote control may be used for the viewer to call up the user

interface menu for the phonebook-like information. The user interface menu for the phonebook-like information provides a search screen to allow the viewer to search the phonebook-like information and to make a phone call to a selected telephone number from the search.

[0066] For security monitoring applications, information from a security monitoring system (e.g., visual or motion based) at a user's premise can be connected to the display controller and can be delivered to and shown in the supplemental display window via a security monitoring user interface menu. For example, video feed from a security camera can be transmitted to the display controller and be displayed in the supplemental display window on the screen. When the supplemental display window is used to show advertisements or other data from the designated application channel, the security monitoring user interface menu may be called up to display in the supplemental display window by a trigger signal (e.g., an alarm signal) or by a selection made by the viewer through either a designated button on the remote control or an icon on the screen.

[0067] Electronic games can be stored on the designated application channel computer server 710 in FIG. 7 and delivered to a user via the designated application channel at the user's request via a fee. Once the gaming option is activated, the customer needs to select the gaming icon on the supplemental display window or a designated button on the remote control to access the available games. There can be a broad range of offering of games. One level of games may be stand alone games and may be played in either of the main and supplemental display windows at the user's choice. Another level of games may be integrated games based on TV broadcasts that have been developed with interactivity in connection with the contents of the TV broadcasts. For example, an enhanced TV game served by the computer server 710 in FIG. 7 may be designed to play with a broadcast football game to allow the

viewer to predict what may happen in the next five minutes of the football game, or compete with the contestants of a game show. Examples of suitable games for the designated application channel include arcade games, quizzes, strategy games, word puzzles, multi-player game on television, betting game on TV (e.g., Casinos, Poker, Bingo), and interactive games.

[0068] In addition, the designated application channel may also be used to provide premium Pay Per View Information (download) for various programming including new movie releases and sporting events.

[0069] Referring to the laser system example in FIG. 5A, a single laser module 510 is provided to produce one or more scanning laser beams 520 that excite light-emitting materials deposited on the screen 501 to produce color images. The one or more scanning laser beams 520 produced by the laser module 510 are modulated to carry images for the two or more display windows in response to the display control signal 245 that carries application channel and TV/Video channel data as illustrated in the example in FIG. 2. Alternatively, two or more different laser modules can be implemented to respectively control different display windows on the screen 501 with one display window per laser module.

[0070] FIG. 10 shows an example of a scanning laser display system where two laser modules 510A and 510B are implemented to project images in two display windows 1010 and 1020 on the screen 501, respectively. The two display windows 1010 and 1020 are separate regions on the screen 501 and do not overlap with each other. The first laser module 510A is used to produce one or more scanning laser beams 520A that excite light-emitting materials in the display window 1010 on the screen 501 to produce color images that are generated specifically for the display window 1010. The second laser module 510B is used to produce one or more scanning laser

beams 520B, that are separate from the beams 520A, to excite light-emitting materials in the display window 1020 on the screen 501 to produce color images that are generated specifically for the display window 1020. Accordingly, two
5 separate display control signals 1031A and 1031B are generated to control the two laser modules 510A and 510B, respectively. The first display control signal 1031A carries the image information for the display window 1010 and the second display control signal 1031A carries the image information for the
10 display window 1020.

[0071] In one implementation, two different display controllers may be provided to generate the first and second display control signals 1031A and 1031B, respectively. FIG. 10 shows a different implementation of the display control by
15 using a single display controller 1030 to generate the first and second display control signals 1031A and 1031B that carry (1) the application channel input 122 and (2) the TV/Video Channel Inputs 120, respectively. The example in FIG. 10 shows two display windows. This configuration of using one
20 laser module per display window can be applied to a system with 3 or more display windows on the screen.

[0072] The different laser modules 510A and 510B can be identical or have different configurations. For example, the laser modules 510A and 510B may be different from each other
25 in one or more aspects such as the number of lasers and scanning laser beams, the scanning rates, and the power levels of the scanning laser beams 520A and 520B. This configuration of using one laser module per display window provides design flexibilities in such a display system.

30 **[0073]** The disclosed and other embodiments and the functional operations described in this specification can be implemented in digital electronic circuitry, or in computer software, firmware, or hardware, including the structures disclosed in this specification and their structural equivalents, or in

combinations of one or more of them. The disclosed and other embodiments can be implemented as one or more computer program products, i.e., one or more modules of computer program instructions encoded on a computer readable medium for
5 execution by, or to control the operation of, data processing apparatus. The computer readable medium can be a machine-readable storage device, a machine-readable storage substrate, a memory device, a composition of matter effecting a machine-readable propagated signal, or a combination of one or more
10 them. The term "data processing apparatus" encompasses all apparatus, devices, and machines for processing data, including by way of example a programmable processor, a computer, or multiple processors or computers. The apparatus can include, in addition to hardware, code that creates an
15 execution environment for the computer program in question, e.g., code that constitutes processor firmware, a protocol stack, a database management system, an operating system, or a combination of one or more of them. A propagated signal is an artificially generated signal, e.g., a machine-generated
20 electrical, optical, or electromagnetic signal, that is generated to encode information for transmission to suitable receiver apparatus.

[0074] A computer program (also known as a program, software, software application, script, or code) can be written in any
25 form of programming language, including compiled or interpreted languages, and it can be deployed in any form, including as a stand alone program or as a module, component, subroutine, or other unit suitable for use in a computing environment. A computer program does not necessarily
30 correspond to a file in a file system. A program can be stored in a portion of a file that holds other programs or data (e.g., one or more scripts stored in a markup language document), in a single file dedicated to the program in question, or in multiple coordinated files (e.g., files that

store one or more modules, sub programs, or portions of code).
A computer program can be deployed to be executed on one
computer or on multiple computers that are located at one site
or distributed across multiple sites and interconnected by a
5 communication network.

[0075] The processes and logic flows described in this
specification can be performed by one or more programmable
processors executing one or more computer programs to perform
functions by operating on input data and generating output.

10 The processes and logic flows can also be performed by, and
apparatus can also be implemented as, special purpose logic
circuitry, e.g., an FPGA (field programmable gate array) or an
ASIC (application specific integrated circuit).

[0076] Processors suitable for the execution of a computer
15 program include, by way of example, both general and special
purpose microprocessors, and any one or more processors of any
kind of digital computer. Generally, a processor will receive
instructions and data from a read only memory or a random
access memory or both. The essential elements of a computer
20 are a processor for performing instructions and one or more
memory devices for storing instructions and data. Generally,
a computer will also include, or be operatively coupled to
receive data from or transfer data to, or both, one or more
mass storage devices for storing data, e.g., magnetic, magneto
25 optical disks, or optical disks. However, a computer need not
have such devices. Computer readable media suitable for
storing computer program instructions and data include all
forms of non volatile memory, media and memory devices,
including by way of example semiconductor memory devices,
30 e.g., EPROM, EEPROM, and flash memory devices; magnetic disks,
e.g., internal hard disks or removable disks; magneto optical
disks; and CD ROM and DVD-ROM disks. The processor and the
memory can be supplemented by, or incorporated in, special
purpose logic circuitry.

[0077] To provide for interaction with a user, the disclosed embodiments can be implemented by using a TV remote control or other user control devices (e.g., a keyboard). Other kinds of devices can be used to provide for interaction with a user as well; for example, feedback provided to the user can be any form of sensory feedback, e.g., visual feedback, auditory feedback, or tactile feedback; and input from the user can be received in any form, including acoustic, speech, or tactile input.

[0078] The disclosed embodiments can be implemented in a computing system that includes a back end component, e.g., as a data server, or that includes a middleware component, e.g., an application server, or that includes a front end component, e.g., a client computer having a graphical user interface or a Web browser through which a user can interact with an implementation of what is disclosed here, or any combination of one or more such back end, middleware, or front end components. The components of the system can be interconnected by any form or medium of digital data communication, e.g., a communication network. Examples of communication networks include a local area network ("LAN"), a wide area network ("WAN"), e.g., the Internet, and a wireless communication network (e.g., a wireless cellular communication network).

[0079] A computer system for implementing the disclosed embodiments can include client computers (clients) and server computers (servers). A client and a server are generally remote from each other and typically interact through a communication network. The relationship of client and server can arise by virtue of computer programs running on the respective computers and having a client-server relationship to each other.

[0080] While this specification contains many specifics, these should not be construed as limitations on the scope of any

invention or of what may be claimed, but rather as descriptions of features specific to particular embodiments. Certain features that are described in this specification in the context of separate embodiments can also be implemented in combination in a single embodiment. Conversely, various features that are described in the context of a single embodiment can also be implemented in multiple embodiments separately or in any suitable subcombination. Moreover, although features may be described above as acting in certain combinations and even initially claimed as such, one or more features from a claimed combination can in some cases be excised from the combination, and the claimed combination may be directed to a subcombination or variation of a subcombination.

[0081] Similarly, while operations are depicted in the drawings in a particular order, this should not be understood as requiring that such operations be performed in the particular order shown or in sequential order, or that all illustrated operations be performed, to achieve desirable results. In certain circumstances, multitasking and parallel processing may be advantageous. Moreover, the separation of various system components in the embodiments described above should not be understood as requiring such separation in all embodiments, and it should be understood that the described program components and systems can generally be integrated together in a single software product or packaged into multiple software products.

[0082] Thus, particular embodiments have been described. Other embodiments are within the scope of the following claims.

CLAIMS

What is claimed is:

1. A method for delivering information to a display,
5 comprising:

establishing a communication link with a display, which receives one or more TV programming channels and an independent designated application channel and includes at least a first display window and a second display window
10 separated from each other without spatial overlap on the screen, to send data of the independent designated application channel to the display, wherein the communication link is separate from one or more communication links that deliver the one or more TV programming channels to the display; and

15 delivering information over the designated application channel to the display to display in the first display window while simultaneously displaying a TV programming channel on the second display window.

20 2. The method as in claim 1, comprising:

providing a viewer control mechanism to allow the viewer to switch the information received from the designated application channel from the first display window to the second display window and switch back at the viewer's choice.

25 3. The method as in claim 2, comprising:

using at least one computer server in communication with a communication network to deliver data of the designated application channel to the display over the communication
30 network;

providing a viewer feedback from the display to the computer server via a display remote control and a user graphic interface through the designated application channel

to allow a viewer to send a viewer request or viewer data to the computer server; and

selecting content of the data in the designated application channel to the display based on the viewer request or data.

4. The method as in claim 3, wherein the viewer request includes viewer preference for advertisements to be delivered through the designated application channel to the viewer's display.

5. The method as claim 3, wherein the viewer data includes viewer demographic information or information on viewer's personal interests.

6. The method as in claim 5, comprising:
controlling the computer server to individualize content of advertisements delivered in the designated application channel based on the viewer demographic information or information on viewer's personal interests.

7. The method as in claim 6, further comprising:
controlling the computer server to deliver different advertisements in the designated application channel to different viewers based on differences on the viewer demographic information or information on viewer's personal interests of the different viewers.

8. The method as in claim 3, comprising:
storing advertisements from one or more advertisers in the computer server; and
delivering the stored advertisements to displays connected to the communication network through the designated application channel to each display.

9. The method as in claim 3, wherein the communication network is a wireless communication network, and the designated application channel is provided through a wireless communication link between the communication network and the display.

10. The method as in claim 9, wherein the wireless communication network is a cellular network.

11. The method as in claim 9, wherein the wireless communication network is a WiFi network under an IEEE 802.11 standard.

12. The method as in claim 9, wherein the wireless communication network is a WiMax network.

13. The method as in claim 9, comprising:
storing data of the designated application channel received at the display in a local memory in the display; and
retrieving stored data from the local memory to project on the display.

14. The method as in claim 13, comprising:
controlling downloading data of the designated application channel through the wireless communication network to the local memory during one or more time periods when communication traffic is low.

15. The method as in claim 1, further comprising:
delivering an application through the designated application channel to the display to allow a viewer to use a service provided by the application.

16. The method as in claim 15, wherein the service of the application is to a control of an appliance connected on the Internet.

5 17. The method as in claim 15, wherein the service of the application is to provide a telephone call or a video conference call.

10 18. The method as in claim 15, wherein the service of the application is to provide an electronic game to the viewer at the viewer's choice.

15 19. The method as in claim 15, wherein the service of the application is to provide security monitoring of a security system to the viewer.

20 20. The method as in claim 15, wherein the service of the application is to provide phonebook-like information to the viewer.

20

21. The method as in claim 2, comprising:

25 storing data received from the TV programming channel in a local memory in the display when the TV programming channel is switched from the second display window to the first display window and the designated application channel is switched from the first display window to the second display window; and

30 retrieving the stored data of the TV programming channel from the local memory to display on the second display window when the TV programming channel is switched to the second display window and the designated application channel data is switched to the first display window.

22. The method as in claim 1, comprising:

storing data received from the designated application channel in a local memory in the display; and

retrieving the stored data from the local memory to display on the screen.

5

23. The method as in claim 1, wherein the display is a plasma flat panel display, a LCD flat panel display, a field emission display (FED) flat panel or an organic light emitting diode (OLED) flat panel.

10

24. The method as in claim 1, wherein the display is a CRT projection display, a LCD projection display, a digital light processing (DLP) projection display, a digital direct drive image light amplifier (D-ILA) projection display, or a liquid crystal on silicon (LCOS) projection display.

15

25. The method as in claim 1, wherein the display is a scanning beam fluorescent or phosphorescence display.

20

26. The method as in claim 1, comprising:
linking the viewer to a website selling a product or service through the independent designated application channel when the viewer selects the product or service on the TV set displaying the designated application channel.

25

27. A display system, comprising:
a screen to display images;
at least one TV and video input to receive a TV or video input channel for display on the screen;

30

a designated application channel receiver to receive a designated application channel that is independent from a broadcast TV programming channel;

a local memory that stores data received in the designated application channel; and

a display controller to control each frame displayed on the screen to have a first display window at a first location on the screen that displays the TV or video input channel and a second window at a second location without overlap with the first display window that displays the stored data in the designated application channel,

wherein the display controller includes a switch mechanism to switch displayed contents between the first and the second display windows.

28. The system as in claim 27, wherein the designated application channel receiver is a wireless receiver which receives a wireless signal from a wireless communication network that carries the designated application channel.

29. The system as in claim 28, wherein the wireless communication network is a cellular network.

30. The system as in claim 28, wherein the wireless communication network is a WiFi network under an IEEE 802.11 standard.

31. The system as in claim 28, wherein the wireless communication network is a WiMax network.

32. The system as in claim 27, wherein the screen is a plasma flat panel, a LCD flat panel, a field emission display (FED) flat panel or an organic light emitting diode (OLED) flat panel.

33. The system as in claim 27, wherein the screen is a screen of a CRT projection display, a LCD projection display, a digital light processing (DLP) projection display, a digital

direct drive image light amplifier (D-ILA) projection display, or a liquid crystal on silicon (LCOS) projection display.

34. The system as in claim 27, comprising:

5 an optical module to produce at least one scanning optical beam to the screen,

wherein the screen comprises fluorescent or phosphorescence stripes that emit light under optical excitation of the at least one scanning optical beam to form
10 images by the emitted light.

35. A system, comprising:

a communication network to provide communications to devices in communication with the communication network;

15 a designated application channel computer server in communication with the communication network to send out data of a designated application channel that is independent from a broadcast TV programming channel; and

a display system comprising a designated application
20 channel receiver in communication with the communication network to receive the data of the designated application channel, a local memory to store the received data, a screen to display images, a display controller to retrieve the stored data from the local memory and to display the retrieved data
25 on the screen, and a TV programming receiver to receive the broadcast TV programming channel,

wherein the display controller operates to control each frame displayed on the screen to simultaneously display the stored data in the designated application channel and the
30 broadcast TV programming channel on the screen.

36. The system as in claim 35, wherein the display controller to control each frame displayed on the screen to have a first display window at a first location on the screen

that displays the broadcast TV programming channel and a second window at a second location without overlap with the first display window that displays the stored data in the designated application channel.

5

37. A method for sending TV advertisements to TV viewers, comprising:

delivering a designated application channel, that is separated from TV programming channels, through a communication network to networked displays equipped to receive the designated application channel and TV programming channels; and

using one or more computer servers in communication with the communication network to supply selected TV advertisements over the designated application channel without TV programming to each of the networked displays based on viewer profile information of one or more TV viewers associated with the respective networked display.

20 38. The method as in claim 37, comprising:

storing a collection of TV advertisements in the one or more computer servers; and

selecting one or more TV advertisements from the stored collection based on the viewer profile information as the selected TV advertisements.

39. The method as in claim 38, comprising:

charging an advertiser a fee for placing one or more TV advertisements from the advertiser in the stored collection.

30

40. The method as in claim 38, further comprising:

distributing the displays equipped to receive the designated application channel and TV programming channels to TV viewers for free or at a nominal charge in exchange for

delivery of the designated application channel to the TV viewers and for the viewer profile information.

41. The method as in claim 38, comprising:

5 distributing a networked display equipped to receive the designated application channel and TV programming channels to a TV viewer for an initial charge in exchange for delivery of the designated application channel to the TV viewer and for the viewer profile information; and

10 refunding the TV viewer at least a portion of the initial charge in installments or in a sum after a period of delivering the designated application channel to the TV viewer.

15 42. The method as in claim 38, comprising:

charging an advertiser a fee each time when a TV advertisement from the advertiser in the stored collection is delivered to a TV viewer.

20 43. The method as in claim 37, comprising:

updating the viewer profile information from data collected from each TV viewer through the designated application channel; and

25 adjusting selected TV advertisements delivered to a TV viewer based on the updated viewer profile information of the TV viewer.

44. The method as in claim 37, comprising:

30 receiving a request for TV advertisements from a TV viewer through the designated application channel; and

overriding a pre-determined schedule for delivery to the requesting TV viewer based on the viewer profile information of the requesting TV viewer to deliver the requested TV advertisements to the requesting TV viewer.

45. The method as in claim 37, comprising:

using the designated application channel to allow a TV
viewer to access a service application stored on the one or
5 more computer servers.

46. The method as in claim 45, wherein the service
application includes a video conference call service.

10 47. The method as in claim 45, wherein the service
application includes a remote control of an on-line appliance
connected to the communication network.

15 48. The method as in claim 45, wherein the service
application includes an on-line game from the one or more
computer servers.

20 49. The method as in claim 45, wherein the service
application includes an on-line phonebook from the one or more
computer servers.

50. The method as in claim 45, wherein the service
application includes monitoring a security system.

FIG. 1




FIG. 2




FIG. 3A
Normal Display Mode




FIG. 3B
Application Display Mode




FIG. 4B




FIG. 4A




FIG. 4D




FIG. 4C




FIG. 4E




FIG. 4F




FIG. 5A




FIG. 5B





FIG. 6




FIG. 8

Graphic User Interface





FIG. 9A




FIG. 9B





FIG. 10



INTERNATIONAL SEARCH REPORT

International application No.
PCT/US2008/057763**A. CLASSIFICATION OF SUBJECT MATTER*****H04N 5/445(2006.01)i***

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 8 H04N

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Korean Utility models and applications for Utility models since 1975

Japanese Utility models and applications for Utility models since 1975

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

eKIPASS (KIPO internal): "application, advertisement, deliver, TV program, display"

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 6463585 B1 (JOHN S. HENDRICKS et al.) 08 October 2002 See abstract; column 1, line 1 - column 7, line 19; claims 1-26; figures 3 and 4a.	1-50
Y	KR 10-2001-0097415 A (PARK, JOO SANG) 08 November 2001 See abstract; claims 1-18; figures 2, 3, and 5.	1-50
A	US 2002-0124250 A1 (ANDREW M. PROEHL et al.) 05 September 2002 See abstract; paragraphs [0001]-[0038]; figure 1.	1-50
A	WO 02-33970 A1 (OPENTV, CORP.) 25 April 2002 See abstract; claims 1-47; figures 1 and 3.	1-50



Further documents are listed in the continuation of Box C.



See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

27 JUNE 2008 (27.06.2008)

Date of mailing of the international search report

27 JUNE 2008 (27.06.2008)

Name and mailing address of the ISA/KR


Korean Intellectual Property Office
Government Complex-Daejeon, 139 Seonsa-ro, Seo-
gu, Daejeon 302-701, Republic of Korea

Facsimile No. 82-42-472-7140

Authorized officer

Yoon, Yeomin

Telephone No. 82-42-481-8515



INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No.

PCT/US2008/057763

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 6463585 B1	08.10.2002	AT 176841 E	15.03.1999
		AT 177277 E	15.03.1999
		AT 183352 E	15.08.1999
		AT 190180 E	15.03.2000
		AT 192005 E	15.05.2000
		AT 197366 E	15.11.2000
		AT 197659 E	15.12.2000
		AT 199294 E	15.03.2001
		AT 214534 E	15.03.2002
		AT 219615 E	15.07.2002
		AT 220840 E	15.08.2002
		AT 221714 E	15.08.2002
		AT 237906 E	15.05.2003
		AT 240021 E	15.05.2003
		AT 251370 E	15.10.2003
		AT 256365 E	15.12.2003
		AT 262251 E	15.04.2004
		AT 278294 E	15.10.2004
		AT 281041 E	15.11.2004
		AT 283608 E	15.12.2004
		AT 289148 E	15.02.2005
		AT 352170 E	15.02.2007
		AU 1995-14306 A1	19.06.1995
		AU 1997-44407 B2	29.01.1998
		AU 1997-45325 B2	05.02.1998
		AU 1998-60667 B2	04.06.1998
		AU 1998-60668 B2	04.06.1998
		AU 1999-33776 A1	25.10.1999
		AU 1999-33776 B2	25.10.1999
		AU 1997-44407 A1	29.01.1998
		AU 1997-45325 A1	05.02.1998
		AU 1994-57329 A1	04.07.1994
		AU 1994-57330 A1	04.07.1994
		AU 1994-57331 A1	04.07.1994
		AU 1994-57332 A1	04.07.1994
		AU 1994-57363 A1	04.07.1994
		AU 1994-58458 A1	22.06.1994
		AU 1994-58698 A1	04.07.1994
		AU 1998-60668 A1	04.06.1998
		AU 691479 B2	21.05.1998
		AU 692427 B2	11.06.1998
		AU 692428 B2	11.06.1998
		AU 693148 B2	25.06.1998
		AU 693775 B2	09.07.1998
		AU 712157 B2	28.10.1999
		AU 715683 B2	10.02.2000
		AU 716182 B2	24.02.2000
		AU 716184 B2	24.02.2000
		AU 754241 B2	07.11.2002
		BR 9307619 A	15.06.1999
		BR 9307620 A	10.08.1999

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No.

PCT/US2008/057763

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
		BR 9307621 A	15.06.1999
		BR 9307622 A	15.06.1999
		BR 9307623 A	16.05.2000
		BR 9307624 A	15.06.1999
		BR 9307625 A	31.08.1999
		BR 9408211 A	26.08.1997
		BR 9909391 A	11.06.2002
		CA 2151456 C	02.03.2004
		CA 2151456 AA	23.06.1994
		CA 2151456 C	23.06.1994
		CA 2151457 C	29.06.2004
		CA 2151458 AA	23.06.1994
		CA 2151458 C	24.02.2004
		CA 2151459 C	02.03.2004
		CA 2151460 AA	23.06.1994
		CA 2151460 C	24.02.2004
		CA 2151461 C	21.09.2004
		CA 2151462 AA	23.06.1994
		CA 2151462 C	24.02.2004
		CA 2177153 AA	08.06.1995
		CA 2177153 C	16.09.2003
		CA 2271552 AA	09.06.1994
		CA 2271552 C	28.11.2006
		CA 2271555 AA	09.06.1994
		CA 2271555 C	11.11.2003
		CA 2326397 AA	14.10.1999
		CA 2326397 C	11.09.2007
		CA 2326397 C	14.10.1999
		CA 2345161 AA	09.06.1994
		CA 2410389 AA	09.06.1994
		CA 2410389 C	23.03.2004
		CA 2410389 A1	09.06.1994
		CA 2431951 AA	08.06.1995
		CA 2431951 C	22.02.2005
		CA 2431951 C	08.06.1995
		CA 2444170 AA	23.06.1994
		CA 2445176 AA	23.06.1994
		CA 2445176 C	06.09.2005
		CA 2445176 C	23.06.1994
		CA 2445187 AA	23.06.1994
		CA 2445187 C	01.05.2007
		CA 2445187 C	23.06.1994
		CA 2445201 AA	23.06.1994
		CA 2445201 C	20.11.2007
		CA 2445201 C	23.06.1994
		CA 2445287 AA	23.06.1994
		CA 2445287 C	22.02.2005
		CA 2445287 C	23.06.1994
		CA 2447895 AA	23.06.1994
		CA 2447895 C	22.05.2007
		CA 2447895 C	23.06.1994

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No.

PCT/US2008/057763

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
		CA 2460634 AA	23.06.1994
		CA 2461105 AA	09.06.1994
		CA 2553120 AA	23.06.1994
		CA 2590528 AA	14.10.1999
		CN 1090451	03.08.1994
		CN 1090452 A	03.08.1994
		CN 1090453	03.08.1994
		CN 1090454 A	03.08.1994
		CN 1093211 A	05.10.1994
		CN 1096151 A	07.12.1994
		CN 1112808 C	25.06.2003
		CN 1118197 C	13.08.2003
		CN 1121788 C	17.09.2003
		CN 1156161 C	30.06.2004
		CN 1179563 C	08.12.2004
		CN 1181680 C	22.12.2004
		CN 1181682 C	22.12.2004
		CN 1184812 C	12.01.2005
		CN 1189033 C	09.02.2005
		CN 1192617 C	09.03.2005
		CN 1217286 C	31.08.2005
		CN 1223525	21.07.1999
		CN 1259826	12.07.2000
		CN 1259827 A	12.07.2000
		CN 1275866 A	06.12.2000
		CN 1276682 A	13.12.2000
		CN 1276683	13.12.2000
		CN 1276684 A	13.12.2000
		CN 1276685	13.12.2000
		CN 1276686 A	13.12.2000
		CN 1280446 A	17.01.2001
		CN 1284814	21.02.2001
		CN 1284815 A	21.02.2001
		CN 1285555 A	28.02.2001
		CN 1285684 A	28.02.2001
		CN 1303569 A	11.07.2001
		CN 1805540 A	19.07.2006
		DE 69323560 C0	25.03.1999
		DE 69323560 T2	23.09.1999
		DE 69323562 C0	25.03.1999
		DE 69323562 T2	23.09.1999
		DE 69323767 C0	08.04.1999
		DE 69323767 T2	21.10.1999
		DE 69326020 C0	16.09.1999
		DE 69326020 T2	06.04.2000
		DE 69327966 C0	06.04.2000
		DE 69327966 T2	16.11.2000
		DE 69328441 C0	25.05.2000
		DE 69328441 T2	25.01.2001
		DE 69329627 C0	07.12.2000
		DE 69329627 T2	13.06.2001

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No.

PCT/US2008/057763

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
		DE 69329949 C0	29.03.2001
		DE 69329949 T2	07.06.2001
		DE 69331715 T2	24.10.2002
		DE 69332049 C0	25.07.2002
		DE 69332049 T2	27.02.2003
		DE 69332177 C0	05.09.2002
		DE 69332177 T2	08.05.2003
		DE 69332895 C0	22.05.2003
		DE 69332895 T2	05.02.2004
		DE 69332962 C0	12.06.2003
		DE 69332962 T2	19.02.2004
		DE 69332962 T3	28.12.2006
		DE 69333457 T2	25.11.2004
		DE 69333644 C0	04.11.2004
		DE 69333644 T2	13.10.2005
		DE 69333680 C0	02.12.2004
		DE 69333680 T2	18.08.2005
		DE 69333713 C0	30.12.2004
		DE 69333713 T2	21.07.2005
		DE 69333756 C0	17.03.2005
		DE 69333756 T2	17.11.2005
		DE 69333999 C0	18.05.2006
		DE 69333999 T2	16.11.2006
		DE 69334106 C0	08.03.2007
		DE 69334106 T2	06.09.2007
		DE 69426308 C0	21.12.2000
		DE 69426308 T2	21.06.2001
		DE 69902158 C0	22.08.2002
		DE 69902158 T2	03.04.2003
		DE 69911817 C0	06.11.2003
		DE 69911817 T2	01.07.2004
		DE 69913571 T2	05.08.2004
		EP 0673578 B1	03.03.1999
		EP 0673579 B1	21.02.2001
		EP 0673580 B1	17.02.1999
		EP 0673581 B1	19.04.2000
		EP 0673582 B1	01.03.2000
		EP 0673583 B1	11.08.1999
		EP 0674824 B1	17.02.1999
		EP 0732031 B1	15.11.2000
		EP 0822718 A1	04.02.1998
		EP 0822718 B1	19.06.2002
		EP 0849948 A2	24.06.1998
		EP 0849948 B1	13.03.2002
		EP 0849948 B2	22.08.2007
		EP 0852442 A1	08.07.1998
		EP 0852442 B1	02.11.2000
		EP 0856993 A2	05.08.1998
		EP 0856993 B1	31.07.2002
		EP 0856994 A2	05.08.1998
		EP 0856994 B1	17.03.2004

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No.

PCT/US2008/057763

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
		EP 0862328 A1	02.09.1998
		EP 0862328 B1	16.04.2003
		EP 0884907 A1	16.12.1998
		EP 0909095 A1	14.04.1999
		EP 0909095 B1	27.10.2004
		EP 0910218 A2	21.04.1999
		EP 0910218 B1	29.09.2004
		EP 0912058 A2	28.04.1999
		EP 0912058 B1	24.11.2004
		EP 0912059 A2	28.04.1999
		EP 0920206 A1	02.06.1999
		EP 0920206 B1	09.02.2005
		EP 0920207 A1	02.06.1999
		EP 0920207 B1	07.05.2003
		EP 0920207 B2	27.09.2006
		EP 0920208 A1	02.06.1999
		EP 0935393 A2	11.08.1999
		EP 0946060 A1	29.09.1999
		EP 0946060 B1	17.01.2007
		EP 0963116 A2	08.12.1999
		EP 1068729 A1	17.01.2001
		EP 1068729 B1	17.07.2002
		EP 1164797 A1	19.12.2001
		EP 1207695 A1	22.05.2002
		EP 1207696 A1	22.05.2002
		EP 1207696 B1	01.10.2003
		EP 1207697 A1	22.05.2002
		EP 1207697 B1	10.12.2003
		EP 1432248 A1	23.06.2004
		EP 1432248 B1	29.03.2006
		EP 0732031 A1	18.09.1996
		EP 0822718 A1	04.02.1998
		EP 0849948 A2	24.06.1998
		EP 0852442 A1	08.07.1998
		EP 0856993 A2	05.08.1998
		EP 0856994 A2	05.08.1998
		EP 0862328 A1	02.09.1998
		EP 0909095 A1	14.04.1999
		EP 0935393 A2	11.08.1999
		EP 0946060 A1	29.09.1999
		EP 0963116 A2	08.12.1999
		EP 1068729 A1	17.01.2001
		EP 1068729 B1	17.07.2002
		EP 1164797 A1	19.12.2001
		EP 1207695 A1	22.05.2002
		EP 1207696 A1	22.05.2002
		EP 1207696 B1	01.10.2003
		EP 1207696 A1	22.05.2002
		EP 1207697 A1	22.05.2002
		EP 1207697 B1	10.12.2003
		EP 1432248 A1	23.06.2004

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No.

PCT/US2008/057763

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
		EP 1432248 B1	29.03.2006
		EP 1432248 A1	23.06.2004
		EP 0673578 A1	27.09.1995
		EP 0673578 B1	03.03.1999
		EP 0673579 A1	27.09.1995
		EP 0673579 B1	21.02.2001
		EP 0673580 A1	27.09.1995
		EP 0673580 B1	17.02.1999
		EP 0673581 A1	27.09.1995
		EP 0673581 B1	19.04.2000
		EP 0673582 B1	01.03.2000
		EP 0673582 A1	27.09.1995
		EP 0673583 A1	27.09.1995
		EP 0673583 B1	11.08.1999
		EP 0674824 A1	04.10.1995
		EP 0674824 B1	17.02.1999
		EP 0732031 A1	18.09.1996
		EP 0732031 B1	15.11.2000
		EP 0822718 B1	19.06.2002
		EP 0822718 A1	04.02.1998
		EP 0849948 A2	24.06.1998
		EP 0849948 A3	08.07.1998
		EP 0849948 B1	13.03.2002
		EP 0849948 B2	22.08.2007
		EP 0852442 B1	02.11.2000
		EP 0852442 A1	08.07.1998
		EP 0856993 A2	05.08.1998
		EP 0856993 A3	19.08.1998
		EP 0856993 B1	31.07.2002
		EP 0856994 B1	17.03.2004
		EP 0856994 A2	05.08.1998
		EP 0856994 A3	19.08.1998
		EP 0862328 A1	02.09.1998
		EP 0862328 B1	16.04.2003
		EP 0884907 A1	16.12.1998
		EP 0909095 A1	14.04.1999
		EP 0909095 B1	27.10.2004
		EP 0910218 B1	29.09.2004
		EP 0910218 A2	21.04.1999
		EP 0910218 A3	19.05.1999
		EP 0912058 A2	28.04.1999
		EP 0912058 A3	19.05.1999
		EP 0912058 B1	24.11.2004
		EP 0912059 A2	28.04.1999
		EP 0912059 A3	19.05.1999
		EP 0920206 A1	02.06.1999
		EP 0920206 B1	09.02.2005
		EP 0920207 B1	07.05.2003
		EP 0920207 B2	27.09.2006
		EP 0920207 A1	02.06.1999
		EP 0920208 A1	02.06.1999

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No.

PCT/US2008/057763

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
		EP 0935393 A2	11.08.1999
		EP 0935393 A3	18.08.1999
		EP 0946060 A1	29.09.1999
		EP 0946060 B1	17.01.2007
		EP 0963116 A2	08.12.1999
		EP 0963116 A3	15.12.1999
		ES 2128551 T3	16.05.1999
		ES 2129116 T3	01.06.1999
		ES 2129621 T3	16.06.1999
		ES 2138656 T3	16.01.2000
		ES 2145119 T3	01.07.2000
		ES 2145821 T3	16.07.2000
		ES 2151590 T3	01.01.2001
		ES 2152712 T3	01.02.2001
		ES 2154291 T3	01.04.2001
		ES 2172038 T3	16.09.2002
		ES 2178730 T3	01.01.2003
		ES 2180088 T3	01.02.2003
		ES 2181410 T3	16.02.2003
		HK 1012480 A1	15.03.2002
		HK 1012481 A1	22.09.2000
		HK 1012482 A1	22.09.2000
		HK 1012483 A1	22.09.2000
		HK 1012484 A1	22.09.2000
		HK 1014823 A1	28.09.2001
		HK 1021604 A1	30.05.2003
		HK 1021679 A1	31.08.2001
		HK 1021680 A1	14.01.2005
		HK 1021681 A1	05.03.2004
		HK 1023880 A1	08.04.2004
		HK 1023887 A1	24.01.2003
		HK 1048038 A1	18.06.2004
		HK 1066956 A1	14.07.2006
		IL 107908 A0	07.12.1993
		IL 107909 A0	12.04.1994
		IL 107909 A1	15.04.1997
		IL 107911 A0	12.04.1994
		IL 107911 A1	30.09.1997
		IL 107913 A0	12.04.1994
		IL 107913 A1	15.04.1997
		IL 111859 A0	15.03.1995
		IL 111859 A1	10.12.2003
		IL 119479 A0	10.01.1997
		IL 119479 A1	20.11.1997
		IL 120225 A0	10.06.1997
		IL 120225 A1	17.08.1999
		IL 120300 A1	14.08.2002
		IL 120300 A0	10.06.1997
		IL 120423 A0	13.07.1997
		IL 120423 A1	14.07.1999
		IL 120666 A1	31.12.1999

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No.

PCT/US2008/057763

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
		IL 120666 A0	14.08.1997
		IL 127601 A0	28.10.1999
		IL 127601 A1	01.12.2002
		IL 127602 A0	28.10.1999
		IL 127602 A1	12.03.2003
		IL 128390 A0	31.01.2000
		IL 128390 A1	14.08.2002
		IL 138805 A0	31.10.2001
		IL 138805 A1	20.11.2005
		JP 08-506938	23.07.1996
		JP 08-506939	23.07.1996
		JP 08-506940	23.07.1996
		JP 08-506941	23.07.1996
		JP 08-506942	23.07.1996
		JP 08-510869	12.11.1996
		JP 09-510327	14.10.1997
		JP 2002-510948	09.04.2002
		JP 2005-020785	20.01.2005
		JP 2005-027347	27.01.2005
		JP 2005-039852	10.02.2005
		JP 2005-039853	10.02.2005
		JP 2005-057793	03.03.2005
		JP 2002-510948 T2	09.04.2002
		JP 2005-020785 A2	20.01.2005
		JP 2005-027347 A2	27.01.2005
		JP 2005-039852 A2	10.02.2005
		JP 2005-057793 A2	03.03.2005
		JP 3677037 B2	27.07.2005
		JP 3761893 B2	29.03.2006
		JP 3807679 B2	09.08.2006
		JP 3958311 B2	15.08.2007
		JP 3958313 B2	15.08.2007
		JP 3958354 B2	15.08.2007
		JP 3958355 B2	15.08.2007
		JP 3958356 B2	15.08.2007
		JP 3980579 B2	26.09.2007
		JP 8506938 T2	23.07.1996
		JP 8506939 T2	23.07.1996
		JP 8506940 T2	23.07.1996
		JP 8506941 T2	23.07.1996
		JP 8506942 T2	23.07.1996
		JP 8510869 T2	12.11.1996
		JP 9510327 T2	14.10.1997
		KR 10-1995-0704906	20.11.1995
		KR 10-1995-0704908	20.11.1995
		KR 10-1995-0704909	20.11.1995
		KR 10-1995-0704910	20.11.1995
		KR 10-1995-0704911	20.11.1995
		KR 10-1995-0704912	20.11.1995
		KR 10-1996-0706749	09.12.1996
		KR 10-1998-0709982	02.12.1998

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No.

PCT/US2008/057763

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
		KR 10-1998-0709984	02.12.1998
		KR 10-1998-0709986	02.12.1998
		KR 10-1998-0709987	02.12.1998
		KR 10-1998-0709988	02.12.1998
		KR 10-1998-0709989	02.12.1998
		KR 10-1998-0709990	02.12.1998
		KR 10-2001-0034740	25.04.2001
		PA 00009649 A	08.05.2002
		NZ 259147 A	26.05.1997
		NZ 259148 A	26.11.1996
		NZ 278185 A	27.04.1998
		NZ 314438 A	28.07.1998
		NZ 314598 A	28.01.1999
		NZ 329943 A	23.12.1998
		NZ 507649 A	28.03.2003
		RU 2112325 C1	27.05.1998
		RU 2119726 C1	27.09.1998
		RU 2138923 C1	27.09.1999
		RU 2153234 C2	20.07.2000
		RU 2192103 C2	27.10.2002
		RU 2252494 C2	20.05.2005
		TW 447219 B	21.07.2001
		TW 447219 A	21.07.2001
		US 5600364	04.02.1997
		US 6738978	18.05.2004
		US 2002-042923 A1	11.04.2002
		US 2002-104083 A1	01.08.2002
		US 2002-112249 A1	15.08.2002
		US 2003-117445 A1	26.06.2003
		US 2003-145323 A1	31.07.2003
		US 2004-111742 A1	10.06.2004
		US 2005-157217 A1	21.07.2005
		US 2007-183430 AA	09.08.2007
		US 2007-201702 A1	30.08.2007
		US 5559549 A	24.09.1996
		US 5600364 A	04.02.1997
		US 5600573 A	04.02.1997
		US 5659350 A	19.08.1997
		US 5682195 A	28.10.1997
		US 5734853 A	31.03.1998
		US 5798785 A	25.08.1998
		US 5986690 A	16.11.1999
		US 5990927 A	23.11.1999
		US 6052554 A	18.04.2000
		US 6160989 A	12.12.2000
		US 6181335 B1	30.01.2001
		US 6201536 B1	13.03.2001
		US 6408437 B1	18.06.2002
		US 6463585 BA	08.10.2002
		US 6515680 B1	04.02.2003
		US 6539548 B1	25.03.2003

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No.

PCT/US2008/057763

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
		US 6557173 B1	29.04.2003
		US 6738978 B1	18.05.2004
		US 6828993 B1	07.12.2004
		US 7013478 BA	14.03.2006
		US 7017178 BA	21.03.2006
		US 7073187 BA	04.07.2006
		US 7134131 BA	07.11.2006
		US 7168084 BA	23.01.2007
		US 7207053 BA	17.04.2007
		US 7207055 BA	17.04.2007
		US 7260829 BA	21.08.2007
		US 7269841 BA	11.09.2007
		US 7298851 BA	20.11.2007
		WO 94-13107 A1	09.06.1994
		WO 94-14280 A1	23.06.1994
		WO 94-14282 A1	23.06.1994
		WO 94-14284 A1	23.06.1994
		WO 95-15658 A1	08.06.1995
		WO 99-52285 A1	14.10.1999
KR 10-2001-0097415 A	08.11.2001	None	
US 2002-0124250 A1	05.09.2002	None	
WO 02-33970 A1	25.04.2002	AU 2001-10478 A5	29.04.2002
		CA 2426995 AA	25.04.2002
		EP 1327356 A1	16.07.2003